

## **501NG**



- More power, less weight
- User friendly
- Made in France

## High performance output for any engineering projects

- More energy with a lighter casing
- Fit a large range of carriers
- Suitable for wheeled and crawler excavators


## **Low operating costs**

- No tie rods
- Protected automatic grease pump
- Easy maintenance and no constant nitrogen recharge

## **Montabert quality**

- Reinforced and soundproofed housing
- Automatic working pressure adjustment
- Blank firing protection

Weight and dimension	
Weight (kg)	
Breaker operating weight	936
Breaker weight	600
Power cell	310
Dimensions (mm)	
A	1,241
В	567
С	280
D	430
E	51
F	8





Operational information	
Carrier weight range (min - max, t)	9 - 16
Oil flow range (min - max, I/min)	80 - 140
Operating pressure (max, bar)	140
Back pressure (max, bar)	15
Power (kW)	33
Frequency (bpm)	420 - 870
Sound level /10 m (dBA)	128
Automatic greasing	Standard
Pressurization	Pre equiped

CPN
86261328
86803830
86759289
86784758

Spare parts	CPN
Upper bushing	86763588
Lower bushing	86745031
Seal kit	86775665
Retaining pins (x2)	86740552
Retainers	86740560
Maintenance kit - Level 1	86778180
Maintenance kit - Level 2	86778198

Tools				
Weight (kg)	62	62	62	65
Lenght (mm)	1,005	1,005	1,005	1,005
Ø (mm)	106	106	106	106
CPN	86722451	86722469	86722154	86722444

Product designs, specifications and/or data in this document are provided for informational purposes only and are not warranties of any kind. Product designs and/or specifications may be changed at any time without notice. The only warranties that apply to sales of products and services are standard written warranties, which will be furnished upon request.

Komatsu, Joy, Montabert, P&H and other trademarks and service marks used herein are the property of Komatsu Ltd., Komatsu Mining Corp., or their respective owners or licensees.



