

SCREENING BUCKETS SPECIFICATIONS

MODEL	CARRIER SIZE (MIN)		HYDRAULIC FLOW MIN-MAX	MAX HYDRAULIC PRESSURE*	VOLUME ISO / SAE	SCREENING AREA	WIDTH	DEPTH	HEIGHT	STANDARD WEIGHT
	EXCAVATOR	LOADER	L/MIN	BAR	M ³	M ²	CM	CM	CM	KG
EL 2085	3	1	25 - 35	110	0.15 - 0.18	0.2	109	63	64	240
EP 3150	14	7	55 - 95	210	1.0 - 1.1	1.1	190	123	119	1,280
EP 4150	18	9	80 - 110	210	1.3 - 1.4	1.4	190	123	139	1,500
EE 3160	25	12	155 - 235	210	2.1 - 2.4	1.5	200	169	158	2,470
EE 4160	30	14	195 - 235	210	2.7 - 3.0	1.8	200	169	180	2,780
EE 3220	35	14	195 - 235	210	3.0 - 3.3	1.9	260	169	158	3,090
EE 4220	40	18	195 - 235	250	3.7 - 4.2	2.5	260	169	180	3,560
EE 4290	N/A	21	195 - 235	250	4.8 - 5.5	3.3	330	175	180	4,620
EX 140	16	N/A	155 - 235	210	0.9 - 1.1	0.8	126	128	137	1,400
PD 2160	25	10	80 - 160	300	1.4 - 1.7	1.1	214	166	137	2,440
PD 3160	30	12	120 - 240	300	2.0 - 2.3	1.5	214	166	160	2,610
XO 2090										
+SB/SC	5	4	32 - 80	300	0.32 - 0.37	0.5	125	97	88	510
+SV	5	4	20 - 40	300	0.32 - 0.37	0.5	125	113	88	385
XO 2150										
+SB/SC	8	5	40 - 80	300	0.52 - 0.60	0.8	185	115	88	730
+SV	8	5	20 - 40	300	0.52 - 0.60	0.7	185	109	88	510
+CM	8	5	50 - 120	250	0.52 - 0.60	N / A	185	125	88	810

Weight is calculated with configuration x001 10/30, comb counter blades, no cleaning scrapers

*with default motors