



DEMOLITION ATTACHMENTS



ROTAR INTERNATIONAL B.V.

Address
Sisalstraat 85
8281 JK Genemuiden (NL)

Phone
+31(0) 38 385 54 71

E-Mail
info@rotar.com

ROTAR.COM



RPG-SERIES ROTAR ORANGE PEEL GRAB

Rapid cycle times combined with a large volume make the Rotar Orange Peel Grab the perfect attachment for transferring scrap. The RPG will move a mountain! Ingenious, reliable, service-friendly. The RPG Series guarantees maximum productivity.

Type RPG	Machine class (t)	Weight (kg)*	Capacity (l)	Max. load (t)	Rotator (t)
4-450	16 - 35	1600	450	8	20
4-600	16 - 35	1675	600	8	20
4-800	16 - 35	1725	800	8	20
6-600	30 - 50	1950	600	10	25
6-800	30 - 50**	2000	800	10	25

* Weight exclusive adapter.

** Max. machine class 6-800 -38 ton for Scrap Processing.
For other applications contact your ROTAR dealer.

*** Technical specifications are subject to change without prior notice.



RRC-SERIES ROTAR RAIL CUTTER

The Rotar Rail Cutter equals enormous capacity. With its fast cycle times and incredible cutting power, the RRC will process tonnes of rail in the blink of an eye!

Type RRC	Machine class (t)	Weight (kg)*	Jaw opening (mm)	Jaw depth (mm)
25	25 - 38	3500	204	111 - 190

* Weight exclusive adapterplate with bracket.

** Technical specifications are subject to change without prior notice.



HPL/HEX-SERIES ROTAR SCREENING DRUM

The Rotar Screening Drum is the innovative solution for screening construction debris, washing decontaminated materials and cleaning up job sites. The rotating drum with interchangeable screens lets you screen the material to your desired size.

Type HEX	Excavator (t)	Weight (kg)*	Capacity (l)	Distance between ribs (mm)
850 S	15 - 20	1200	870	60
1000 S	20 - 25	1700	1050	60
1400 S	25 - 35	2150	1450	60

Type HPL	Wheel loader (t)	Weight (kg)*	Capacity (l)	Distance between ribs (mm)
800 S	6 - 10	875	800	45
1500 S	10 - 13	1700	1500	45
2000 S	13 - 16	2200	2000	45
2500 I	15 - 18	2544	2500	60
3000 I	17 - 20	2780	3000	60

* Weight exclusive adapterplate with bracket.

** Technical specifications are subject to change without prior notice.



EVB/RVB-SERIES ROTAR SEGREGATOR BUCKET

The Rotar Segregator Bucket is a jack of all trades, whether you are breaking up and cleaning paving slabs, clearing construction and demolition sites, or sorting debris and soil – it is the perfect attachment for you.

Type EVB	Machine class (t)	Weight (kg)*	Capacity (l)	Bucket width
EVB 600 S	13 - 18	1130	600	1200
EVB 800 S	16 - 25	1426	800	1560
EVB 1200 S	21 - 35	1965	1200	1610
EVB 1200 I	21 - 35	1950	1200	1610

Type RVB	Machine class (t)	Weight (kg)*	Capacity (l)	Bucket width
RVB 800 S	4.5 - 7.5	860	1025	2060
RVB 950 S	6 - 9	950	1155	2320
RVB 1500 S	7.5 - 10	1500	1650	2440
RVB 2000 I	10 - 12	180	2050	2650
RVB 2300 I	12 - 15	2260	2225	2800

* Weight exclusive adapterplate with bracket.

** Technical specifications are subject to change without prior notice.



ROTAR

GET THE RED CRUSH!



RG-SERIES

ROTAR SORTING / DEMOLITION GRAB

Reliable, service-friendly and extremely strong. The Rotar Grab is proven to be the perfect grab for industrial demolitions and recycling applications. It is fitted with a strong rotating upper head and changeable knives for a longer life.

Type RG	Machine class (t)	Weight (kg)*	Capacity (l)	Closing force (kN)**
5-N	2 - 5	210	100	12
9-N	5 - 9	435	140	26
12-N	10 - 15	900	325	41
15-N	14 - 18	1015	400	41
22-N	16 - 22	1350	530	53
30-N	20 - 30	1600	640	61
40-N	25 - 40	2200	900	79
50-N	35 - 50	2350	1100	80
55-N	45 - 55	3300	1300	100
60-N	50 - 70	3950	1500	115

* Weight exclusive adapterplate with bracket.

** Closing force by 320 Bar.

*** Technical specifications are subject to change without prior notice.

RDC-SERIES

ROTAR DEMOLITION COMBI SHEAR

It is an impressive sight to see teeth crushing and knives cutting through the extremely strong concrete and steel constructions. The new, stable pivot point design, guarantees successful cutting in the long term.

Type RDC	Machine class (t)	Weight (kg)*	Jaw opening (mm)	Cutting force (t)**
20 S	15 - 25	1950	700	63 - 80
25 S	24 - 35	2670	900	68 - 100
32 S	30 - 45	3050	955	85 - 125
42 S	45 - 70	4100	1230	102 - 140

* Weight exclusive adapterplate with bracket.

** Figures given for cycle times and cutting forces are indications only. External factors such as excavator setting, hydraulic infrastructure, quickcouplers and fittings may influence performance.

*** Technical specifications are subject to change without prior notice.

RDP-SERIES

ROTAR DEMOLITION PULVERIZER

Incredible crushing power combined with tremendous cutting power makes the RDP the perfect pulverizer for both primary and secondary demolitions. The RDP Series is fitted with replaceable casting teeth. The design of the teeth guarantees powerful penetration.

Type RDP	Machine class (t)	Weight (kg)*	Jaw opening (mm)	Cutting force (t)**
20 S	15 - 25	2100	900	62 - 100
25 S	22 - 35	2765	1040	70 - 107
32 S	32 - 50	3100	1090	95 - 152
42 S	45 - 70	4500	1290	105 - 195

* Weight exclusive adapterplate with bracket.

** Figures given for cycle times and cutting forces are indications only. External factors such as excavator setting, hydraulic infrastructure, quickcouplers and fittings may influence performance.

*** Technical specifications are subject to change without prior notice.

RSP-SERIES

ROTAR STATIC PULVERIZER

Incredible crushing power combined with tremendous cutting power makes the Rotar Static Pulverizer perfect for secondary demolitions. The RSP's body is assembled from high-grade performance steel and replaceable wear-resistant materials, making it extremely strong.

Type RDP	Machine class (t)	Weight (kg)*	Jaw opening (mm)	Cutting force (t)**
20 S	16 - 25	1950	850	62 - 93
25 S	20 - 30	2350	920	70 - 105
30 S	25 - 35	3170	1120	80 - 127
40 S	32 - 60	4500	1230	115 - 155

* Weight exclusive adapterplate with bracket.

** Figures given for cycle times and cutting forces are indications only. External factors such as excavator setting, hydraulic infrastructure, quickcouplers and fittings may influence performance.

*** Technical specifications are subject to change without prior notice.

RSS-SERIES

ROTAR SCRAP SHEAR

Enormous cutting power and rapid cycle times guarantee incredible productivity. The RSS will cut tonnes of steel in the blink of an eye!

Type RSS	Machine class (t)	Weight (kg)**	Jaw opening (mm)	Cutting force (t)***
10	9 - 13	1260	385	270
20 X	13 - 23	2540	450	578
30	20 - 27	3590	607	664
40	25 - 32	4440	750	813
50	30 - 45	6180	782	955
100	45 - 68	8250	947	1338
100 X	50 - 68	9750	954	1570

* X = 380 bar

** Weight exclusive adapterplate with bracket.

*** Figures given for cycle times and cutting forces are indications only. External factors such as excavator setting, hydraulic infrastructure, quickcouplers and fittings may influence performance.

**** Technical specifications are subject to change without prior notice.

RCC-SERIES

ROTAR CONCRETE CUTTER

The Rotar Concrete Cutter is a real game changer! With his unique combination of fast cycle times and enormous power.

Type RCC	Machine class (t)	Weight (kg)*	Jaw opening (mm)	Cutting force (t)**
20	18 - 25	1950	905	92 - 565
25	20 - 30	2490	1020	96 - 640
30	25 - 35	2850	1115	120 - 800
45	38 - 55	4750	1444	158 - 1422

* Weight exclusive adapterplate with bracket.

** Figures given for cycle times and cutting forces are indications only. External factors such as excavator setting, hydraulic infrastructure, quickcouplers and fittings may influence performance.

*** Technical specifications are subject to change without prior notice.

GET THE RED CRUSH!